

## EMULSION TRANSPORTATION TANK ST 1200



Volume	1 200 l
Insulation	60 mm
Covers	Al - plate
Heating	propane-butane burner
Operating temperature	0 - 85 °C
Pump	centrifugal
Drive	by chassis hydraulics
Spraying bar	max. 2 m

## EMULSION TRANSPORTATION TANK ST 3000 - 5000



Volume	3 000 l	5 000 l
Insulation	80 mm	
Covers	Al -plate or stainless	
Heating	propane-butane / diesel burner	
Operating temperature	0 - 85 °C	
Pump	centrifugal	
Drive	auxiliary engine HATZ	
Spraying bar	max. 3,5 m	

## EMULSION TRANSPORTATION TANK ST COMBI



Emulsion tank capacity	4 000 l
Insulation	80 mm
Covers	Al - plate
Pump	centrifugal
Drive	auxiliary engine HATZ
Spraying bar	max. 3,5 m
Filling hose	10 m - on the drum
Water tank	3 000 l
Possibility of cylindrical sweeping brush attachment	

## BITUMEN COATING SPREADER RŽ 3, 10, 11



Capacity	3 000 l	8 000 l	11 000 l
Insulation	80 mm	100 mm	
Covers	Al - plate		stainless
Heating - diesel burner	direct		indirect
Operating temperature	0 - 80 °C	0 - 190 °C	0 - 190 °C
Pump	gear type		
Mixing device	no		yes
Spraying bar	max. 4 m	max. 5 m	

