

INERT MATERIAL SPREADER SYKO 2, 2,5, 3



Body capacity	2 - 3 m ²
Material excavation	1x worm
Drive	250 mm
Dosing - salt/inert	hydraulics, auxiliary engine
Basic brine/salt ratio	50 - 300 g/m ²
Control	2 - 8 m

Operating speed	3 - 60 km/hod.
Superstructure weight	1 200 - 1 550 kg
Body heating	independent heating (spec. accessories)
Front spreader	included
Rear spreader	special accessories

It can be used for bitumen transport for the rest of the year

INERT MATERIAL SPREADER SYKO 4, 5, 6



Body capacity	4 - 5 m ²
Material excavation	2x worm
Drive	320 mm
Dosing - salt/inert	hydraulics, auxiliary engine
Basic brine/salt ratio	50 - 300 g/m ²
Control	2 - 8 m

Operating speed	3 - 60 km/hod.
Superstructure weight	2 100 - 2 650 kg
Body heating	independent heating (spec. accessories)
Front spreader	included
Rear spreader	special accessories

It can be used for bitumen transport for the rest of the year

INERT MATERIAL SPREADER SYKO 7, 8



Body capacity	6 - 7 m ²
Material excavation	2x worm
Drive	320 mm
Dosing - salt/inert	hydraulics, auxiliary engine
Basic brine/salt ratio	50 - 300 g/m ²
Control	2 - 8 m

Operating speed	3 - 60 km/hod.
Superstructure weight	2 300 - 2 850 kg
Body heating	independent heating (spec. accessories)
Front spreader	included
Rear spreader	special accessories

It can be used for bitumen transport for the rest of the year